

Remache DIN7337


Aplicación

Remaches ciegos de vástago a rotura, cuerpo abierto y cabeza alomada.

Cobre

Open end blind rivets with break pull mandrel and protruding head.


Copper



Remache Cobre cabeza alomada DIN7337.



Código	D Ø (mm)	L (mm)	d 2 (mm)	S (mm)	d 1 (mm)	unds caja	unds cartón
RC306	3,0x 6	6	6,5	1,0-3,5	3,0	1.000	8.000
RC307	3,0x 7	8	6,5	3,5-4,5	3,0	1.000	8.000
RC309	3,0x 9	10	6,5	5,5-6,5	3,0	1.000	8.000
RC312	3,0x 12	12	6,5	7,0-9,0	3,0	1.000	8.000
RC406	4,0x 6	6	8,1	1,5-3,0	4,0	1.000	8.000
RC407	4,0x 7	7	8,1	3,0-4,0	4,0	1.000	8.000
RC410	4,0x 9	10	8,1	6,0-7,0	4,0	1.000	8.000
RC411	4,0x 11	12	8,1	7,0-8,5	4,0	1.000	8.000
RC412	4,0x 12	14	8,1	9,0-11	4,0	1.000	8.000
RC416	4,0x 16	16	8,1	8,5-11,5	4,0	1.000	8.000
RC420	4,0x 20	20	8,1	12,5-16,5	4,0	1.000	8.000
RC508	5,0x 8	8	9,5	1,5-3,0	5	1.000	8.000
RC510	5,0x 10	10	9,5	4,0-6,0	5	1.000	8.000
RC512	5,0x 12	12	9,5	6,0-8,0	5	1.000	8.000
RC514	5,0x 14	14	9,5	8,0-10,0	5	1.000	8.000
RC516	5,0x 16	16	9,5	10,0-13,0	5	1.000	8.000-
RC518	5,0x 18	18	9,5	12,0-15,0	5	1.000	8.000
RC520	5,0x 20	20	9,5	12,0-15,0	5	1.000	8.000



Remache estanco.



Código	LxØ (mm)	d 2 (mm)	S (mm)	d 1 (mm)	unds caja	unds cartón
RE410	4x 10	7,8	2,3-4,2	4,00	1.000	8.000
RE413	4x 13	7,8	4,8-7,2	4,80	1.000	8.000
RE501	5x 9,5	12	1,1-3,7	4,80	1.000	8.000
RE502	5x 12,5	12	5,3-6,7	4,80	1.000	8.000
RA503	5x 15,5	12	8,8-9,7	4,80	1.000	8.000
RA504	5x 18	12	9,8-12,2	4,80	1.000	8.000
RA505	5x 20	12	11,0-14,2	4,80	1.000	8.000

GARANTÍA FESIT



Norma

UNE-EN ISO 15977:2003

