



Remache de ala ancha.



Código	LxØ (mm)	d 2 (mm)	S (mm)	d 1 (mm)	unds caja	unds cartón
RA508	5x 8	12	2,5-4,0	4,80	1.000	8.000
RA510	5x 10	12	4,5-6,0	4,80	1.000	8.000
RA512	5x 12	12	6,0-8,0	4,80	1.000	8.000
RA514	5x 14	12	8,0-10,0	4,80	1.000	8.000
RA516	5x 16	12	10,0-13,0	4,80	1.000	8.000
RA518	5x 18	12	12,0-15,0	4,80	1.000	8.000
RA519	5x 19	12	12,0-16,0	4,80	1.000	8.000
RA521	5x 21	12	14,0-16,0	4,80	1.000	8.000
RA525	5x 25	12	16,0-19,0	4,80	1.000	8.000
RA527	5x 27	12	18,0-21,0	4,80	1.000	8.000
RA530	5x 30	12	20,0-26,0	4,80	1.000	8.000
RA535	5x 35	12	25,0-28,0	4,80	1.000	8.000
RA540	5x 40	12	27,0-32,0	4,80	1.000	8.000

Remache ala ancha

Aplicación

Remaches estanco

Aluminio

GARANTÍA FESIT



Norma

UNE-EN ISO 15977:2003

